

Eagle® Dragway Special Eagle® Drag Radial Eagle® Drag Motorcycle

- Large selection of sizes, compounds and constructions for most applications
- Little break-in required
- Longer lasting to help lower tire expenses
- Superior technology for low E.T. and maximum MPH
- Proven performance over a wide range of track conditions



Eagle Dragway Special

Eagle Drag Radial



Eagle Drag Motorcycle

Top Fuel, Funny Car

| Product Code | Size | Soft To Harder → | Rec. Rim Width* (in.) | Overall Diameter (in.) | Average Circumference (in.) | Section Width (in.) | Tread Width (in.) | Recommended Rim Type | Weight (lbs.) |
|--------------------------|--------------|------------------|-----------------------|------------------------|-----------------------------|---------------------|-------------------|----------------------|---------------|
| D-2D | | | | | | | | | |
| 808-018-081 Matl. No. | 36.0x17.5-16 | 2420 200138 | 16.0 | 36.0 | 115.0 | 21.6 | 17.3 | Beadlock | 48.5 |

Pro Stock

| D-4A | | | | | | | | | |
|--------------------------|--------------|----------------|------|------|-------|------|------|----------|------|
| 808-043-081 Matl. No. | 33.5x17.0-16 | 2199 202393 | 16.0 | 33.2 | 103.0 | 20.8 | 17.4 | Beadlock | 43.1 |
| 808-043-081 Matl. No. | 33.5x17.0-16 | 2200 193251 | 16.0 | 33.8 | 105.0 | 20.8 | 17.4 | Beadlock | 43.1 |

Alcohol, Funny Car, Pro Mod

| | | D-2A | D-1 | D-2 | | | | | | | |
|--------------------------|--------------|------------------|---------------|----------------|------|------|-------|------|------|----------|------|
| 808-117-081 Matl. No. | 34.5x17.0-16 | 1022-3 176052 | | | 16.0 | 34.8 | 109.0 | 21.0 | 17.0 | Beadlock | 42.1 |
| 808-117-081 Matl. No. | 34.5x17.0-16 | | 1490 23530 | | 16.0 | 34.8 | 109.0 | 21.0 | 17.0 | Beadlock | 45.3 |
| 808-276-081 Matl. No. | 36.0x17.0-16 | 1230 164841 | | | 16.0 | 36.2 | 114.0 | 21.4 | 17.0 | Beadlock | 49.9 |
| 808-276-081 Matl. No. | 36.0x17.0-16 | | | 3199 121937 | 16.0 | 36.2 | 114.0 | 21.4 | 17.0 | Beadlock | 48.5 |

Stock, Super Stock

| Product Code | Size | Soft To Harder → | | | | | Rec. Rim Width* (in.) | Overall Diameter (in.) | Average Circumference (in.) | Section Width (in.) | Tread Width (in.) | Weight (lbs.) |
|--------------------------|--------------|------------------|------------------|------------------|----------------|------------------|-----------------------|------------------------|-----------------------------|---------------------|-------------------|---------------|
| | | D-12 | D-4A | D-6 | D-5 | D-3 | | | | | | |
| 808-735-081 Matl. No. | 28.0x9.0-15 | | | | | 2000-4 190166 | 8.0 | 28.0 | 88.0 | 10.7 | 9.0 | 21.3 |
| 808-736-081 Matl. No. | 28.0x10.0-15 | | | | | 2001-4 190824 | 10.0 | 28.0 | 88.0 | 12.0 | 10.0 | 23.1 |
| 808-149-081 Matl. No. | 28.0x10.5-15 | | | | | 2502-4 202897 | 10.0 | 28.0 | 88.0 | 12.5 | 10.7 | 24.4 |
| 808-172-081 Matl. No. | 29.0x9.0-15 | | | | | 2003-4 190799 | 8.0 | 29.0 | 91.0 | 10.9 | 9.0 | 21.0 |
| 808-173-081 Matl. No. | 29.0x10.0-15 | | | | | 2004-4 190800 | 10.0 | 29.0 | 91.0 | 11.8 | 10.0 | 23.0 |
| 808-174-081 Matl. No. | 29.0x11.0-15 | | | | | 2006-4 190164 | 10.0 | 29.0 | 91.0 | 12.8 | 10.9 | 25.1 |
| 808-188-081 Matl. No. | 29.0x12.0-15 | | | | | 2007-4 190165 | 11.0 | 29.0 | 91.0 | 13.9 | 11.8 | 26.3 |
| 808-950-081 Matl. No. | 29.0x13.0-15 | | | | 2008 190827 | | 12.0 | 29.0 | 91.0 | 14.8 | 12.8 | 28.1 |
| 808-717-081 Matl. No. | 30.0x9.0-15 | | 2120 192096 | | | | 8.0 | 30.0 | 94.0 | 11.6 | 9.0 | 25.4 |
| 808-717-081 Matl. No. | 30.0x9.0-15 | | | 1909 23623 | | | 8.0 | 30.7 | 96.5 | 12.4 | 9.0 | 25.0 |
| 808-739-081 Matl. No. | 30.0x10.5-15 | | | 2009 190826 | | | 10.0 | 30.0 | 94.0 | 13.0 | 10.2 | 27.6 |
| 808-719-081 Matl. No. | 30.0x11.5-15 | | | 2016 190823 | | | 10.0 | 30.1 | 94.0 | 13.8 | 11.4 | 29.0 |
| 808-214-081 Matl. No. | 30.0x12.5-15 | | | 2017 190822 | | | 12.0 | 30.2 | 95.0 | 15.2 | 12.4 | 30.2 |
| 808-096-081 Matl. No. | 31.0x13.0-15 | | | 2018 190161 | | | 12.0 | 30.6 | 96.0 | 15.6 | 12.8 | 33.4 |
| 808-097-081 Matl. No. | 31.0x14.0-15 | | | 2019-1 190162 | | | 12.0 | 31.0 | 97.0 | 16.2 | 14.0 | 35.8 |
| 808-710-081 Matl. No. | 31.5x14.0-15 | | 1822 189703 | | | | 12.0 | 31.5 | 99.0 | 16.2 | 14.0 | 32.9 |
| 808-266-081 Matl. No. | 31.5x14.5-15 | | 1823 189702 | | | | 14.0 | 31.8 | 100.0 | 18.2 | 14.7 | 34.1 |
| 808-178-081 Matl. No. | 32.0x14.0-15 | | | 1984-1 23556 | | | 14.0 | 32.4 | 101.0 | 17.0 | 14.4 | 39.3 |
| 808-178-081 Matl. No. | 32.0x14.0-15 | 2080-7 192093 | | | | | 14.0 | 32.4 | 102.0 | 17.1 | 14.4 | 33.2 |
| 808-163-081 Matl. No. | 32.0x14.5-15 | | | 1672-1 23540 | | | 14.0 | 32.8 | 103.0 | 17.7 | 14.8 | 39.4 |
| 808-779-081 Matl. No. | 33.0x14.0-15 | | 1831-2 190758 | | | | 14.0 | 32.7 | 102.0 | 18.3 | 14.0 | 34.9 |
| 808-164-081 Matl. No. | 33.0x14.5-15 | | | 2070 190163 | | | 14.0 | 32.8 | 104.0 | 18.9 | 14.9 | 34.1 |

Motorcycle

| Product Code | Size | Soft To Harder → | | | | Rec. Rim Width* (in.) | Overall Diameter (in.) | Average Circumference (in.) | Section Width (in.) | Tread Width (in.) | Weight (lbs.) |
|--------------------------|--------------|------------------|------------------|----------------|------------------|-----------------------|------------------------|-----------------------------|---------------------|-------------------|---------------|
| | | D-9 | D-6 | D-5 | D-3 | | | | | | |
| 808-036-919 Matl. No. | 23.5x4.5-18 | | | | | 2.5 | 23.3 | 73.5 | 3.3 | 4.3 | 5.1 |
| 808-351-919 Matl. No. | 25.0x5.5-18 | | | | 2084-8 192095 | 5.0 | 25.4 | 80.0 | 6.1 | 5.3 | 9.7 |
| 808-891-919 Matl. No. | 25.0x7.0-18 | | 2980-8 103310 | | 2982-8 103311 | 6.0 | 25.4 | 80.0 | 7.0 | 6.6 | 11.3 |
| 808-204-919 Matl. No. | 26.0x9.0-15 | | | | 2085 192094 | 7.0 | 26.1 | 82.0 | 10.0 | 8.7 | 14.4 |
| 808-194-919 Matl. No. | 26.0x10.0-15 | 2175 191717 | | | | 9.0 | 26.4 | 83.0 | 11.6 | 10.0 | 20.3 |
| 808-950-081 Matl. No. | 29.0x13.0-15 | | | 2008 190827 | | 12.0 | 29.0 | 91.0 | 14.8 | 12.8 | 28.1 |

Super Gas, Super Street

| Product Code | Size | D-1 | D-4A | D-6 | D-5 | Rec. Rim Width* (in.) | Overall Diameter (in.) | Average Circumference (in.) | Section Width (in.) | Tread Width (in.) | Weight (lbs.) |
|--------------------------|--------------|--------------------|--------------------|---------------|------------------|-----------------------|------------------------|-----------------------------|---------------------|-------------------|---------------|
| | | | | | | | | | | | |
| 808-178-081 Matl. No. | 32.0x14.0-15 | 1160-1,3 164658 | | | | 14.0 | 32.4 | 102.0 | 17.0 | 14.4 | 34.2 |
| 808-163-081 Matl. No. | 32.0x14.5-15 | 2251-1,3 193643 | | | | 14.0 | 32.8 | 103.0 | 17.7 | 14.8 | 34.9 |
| 808-184-081 Matl. No. | 32.0x16.0-15 | 2252-1,3 193644 | | | | 15.0 | 32.4 | 102.0 | 18.4 | 16.0 | 35.3 |
| 808-260-081 Matl. No. | 33.0x15.0-15 | 2253-1,3 193645 | | | | 14.0 | 33.2 | 104.0 | 17.5 | 15.0 | 35.3 |
| 808-178-081 Matl. No. | 32.0x14.0-15 | | | | 1984-1 23556 | 14.0 | 32.4 | 101.0 | 17.0 | 14.4 | 39.3 |
| 808-163-081 Matl. No. | 32.0x14.5-15 | | | | 1672-1 23540 | 14.0 | 32.8 | 103.0 | 17.7 | 14.8 | 39.4 |
| 808-184-081 Matl. No. | 32.0x16.0-15 | | | | 1408-1 23558 | 15.0 | 32.4 | 102.0 | 18.4 | 16.0 | 39.6 |
| 808-260-081 Matl. No. | 33.0x15.0-15 | | | | 2078-1 192212 | 14.0 | 33.2 | 104.0 | 17.5 | 15.0 | 40.6 |
| 808-801-081 Matl. No. | 33.5x15.0-15 | | | | 2079-1 192213 | 14.0 | 33.6 | 106.0 | 17.8 | 15.1 | 39.2 |
| 808-031-081 Matl. No. | 32.5x17.0-15 | | 2051-1,3 190102 | | | 15.0 | 32.5 | 100.0 | 20.8 | 17.2 | 41.1 |
| 808-031-081 Matl. No. | 33.0x17.0-15 | | 2053-1 191202 | | | 15.0 | 32.8 | 102.0 | 20.6 | 17.3 | 42.9 |
| 808-031-081 Matl. No. | 33.0x17.0-15 | | | 2556 23509 | | 15.0 | 32.8 | 102.0 | 20.5 | 17.3 | 41.0 |

Competition, Super Comp

| Product Code | Size | Soft To Harder → | | | | Rec. Rim Width* (in.) | Overall Diameter (in.) | Average Circumference (in.) | Section Width (in.) | Tread Width (in.) | Recommended Rim Type | Weight (lbs.) |
|--------------------------|--------------|------------------|------------------|--------------------|------------------|-----------------------|------------------------|-----------------------------|---------------------|-------------------|----------------------|---------------|
| | | D-1 | D-6 | D-7 | D-3 | | | | | | | |
| 808-906-081 Matl. No. | 26.0x8.0-15 | | 2119 192100 | | | 7.0 | 26.3 | 83.0 | 9.5 | 7.8 | | 16.1 |
| 808-725-081 Matl. No. | 30.0x12.0-15 | 2112 191798 | | | | 11.0 | 30.2 | 96.0 | 14.5 | 12.3 | | 29.4 |
| 808-129-081 Matl. No. | 30.0x13.0-15 | 2113 191864 | | | | 12.0 | 30.4 | 96.0 | 15.7 | 13.2 | | 28.6 |
| 808-095-081 Matl. No. | 31.0x12.0-15 | | | 2585 206637 | | 12.0 | 30.8 | 96.5 | 15.2 | 12.0 | | 22.6 |
| 808-097-081 Matl. No. | 31.0x14.0-15 | 1999 194375 | | | | 14.0 | 31.2 | 98.0 | 16.8 | 14.1 | | 31.1 |
| 808-266-081 Matl. No. | 31.5x14.5-15 | | 2121-2 193780 | | | 14.0 | 31.8 | 100.0 | 18.2 | 14.7 | | 34.2 |
| 808-163-081 Matl. No. | 32.0x14.5-15 | 1911 193992 | | | | 14.0 | 32.2 | 101.0 | 17.7 | 15.0 | | 34.1 |
| 808-921-081 Matl. No. | 33.0x12.0-15 | | | 1288-2 23654 | 1913-2 189853 | 12.0 | 32.4 | 102.0 | 16.5 | 12.3 | | 28.8 |
| 808-821-081 Matl. No. | 33.0x13.0-15 | | | | 1915-2 189823 | 12.0 | 33.0 | 102.0 | 17.1 | 13.3 | | 29.9 |
| 808-779-081 Matl. No. | 33.0x14.0-15 | | | 2117-2,3 192098 | | 14.0 | 32.4 | 102.0 | 18.3 | 14.0 | | 30.8 |
| 808-164-081 Matl. No. | 33.0x14.5-15 | | 2070 190163 | | | 14.0 | 32.8 | 104.0 | 18.9 | 14.9 | | 34.1 |
| 808-942-081 Matl. No. | 33.0x16.0-15 | | 2052 190167 | | | 15.0 | 32.8 | 102.0 | 19.6 | 16.1 | | 38.0 |
| 808-942-081 Matl. No. | 33.0x16.0-15 | 2071 196201 | | | | 15.0 | 32.4 | 104.0 | 19.9 | 16.3 | | 39.6 |
| 808-031-081 Matl. No. | 33.0x17.0-15 | 2072 191878 | | | | 15.0 | 32.4 | 104.0 | 20.5 | 17.4 | | 39.5 |
| 808-801-081 Matl. No. | 33.5x15.0-15 | | 2118-3 192214 | | | 14.0 | 33.5 | 105.0 | 17.8 | 15.1 | | 35.8 |
| 808-043-081 Matl. No. | 33.5x17.0-16 | 2032 23522 | | | | 16.0 | 33.8 | 105.0 | 21.1 | 16.8 | Beadlock | 39.1 |

Outlaw

| Product Code | Size | Soft To Harder → | | Rec. Rim Width* (in.) | Overall Diameter (in.) | Average Circumference (in.) | Section Width (in.) | Tread Width (in.) | Recommended Rim Type | Weight (lbs.) |
|--------------------------|---------------|------------------|------------------|-----------------------|------------------------|-----------------------------|---------------------|-------------------|----------------------|---------------|
| | | D-4B | D-3 | | | | | | | |
| 808-149-081 Matl. No. | 28.0x10.5-15 | | 2502 202897 | 10.0 | 28.0 | 88.0 | 12.5 | 10.7 | | 24.4 |
| 808-739-081 Matl. No. | 30.0x10.5-15 | | 1790-1 188803 | 10.0 | 30.0 | 94.0 | 13.0 | 10.2 | | 31.2 |
| 808-400-082 Matl. No. | 33.0x10.5W-15 | | 2365-1 199427 | 15.0 | 32.8 | 103.0 | 17.9 | 11.5 | Beadlock | 35.5 |

Radial

| Product Code | Size | Soft To Harder → | | | | Rec. Rim Width* (in.) | Overall Diameter (in.) | Average Circumference (in.) | Section Width (in.) | Tread Width (in.) | Weight (lbs.) |
|--------------------------|--------------|------------------|------------------|------------------|-----|-----------------------|------------------------|-----------------------------|---------------------|-------------------|---------------|
| | | D-4B | D-4A | D-4 | D-5 | | | | | | |
| 388-717-097 Matl. No. | 30.0x9.0-15 | | 6569-4 185469 | 6568-4 185468 | | 9.0 | 29.7 | 93.0 | 12.0 | 9.0 | 26.0 |
| 388-717-097 Matl. No. | 30.0x9.0-15 | 6575-4 188637 | 6502-4 182712 | 6303-4 165044 | | 9.0 | 30.0 | 93.5 | 12.0 | 9.0 | 26.1 |
| 388-178-097 Matl. No. | 32.0x14.0-15 | | | 6892 198162 | | 14.0 | 32.2 | 101.0 | 17.2 | 13.8 | 31.0 |
| 388-164-097 Matl. No. | 33.0x14.5-15 | | | 6894 198150 | | 14.0 | 33.0 | 103.8 | 17.4 | 14.5 | 35.0 |

Front Runner® Eagle® Land Speed

- Lightweight design for lower rolling resistance
- Tubeless construction means lightweight performance and less maintenance
- Longer life helps improve cost effectiveness



**Eagle Drag
Front Runner**

**Eagle Top Fuel
Front Runner**

Front Runner

| Product Code | Size | Soft To Harder → | | | | Rec. Rim Width* (in.) | Overall Diameter (in.) | Average Circumference (in.) | Section Width (in.) | Tread Width (in.) | Weight (lbs.) |
|--------------------------|-------------|------------------|--|------------------|--|-----------------------|------------------------|-----------------------------|---------------------|-------------------|---------------|
| | | Hard | | | | | | | | | |
| 808-243-089 Matl. No. | 23.0x5.0-15 | | | 1961 189891 | | 4.0 | 23.0 | 72.7 | 6.8 | 5.0 | 12.2 |
| 808-730-089 Matl. No. | 24.0x5.0-15 | | | 1962 189955 | | 4.0 | 24.0 | 75.8 | 6.8 | 5.0 | 11.3 |
| 808-028-089 Matl. No. | 25.0x4.5-15 | | | 2981 23505 | | 4.0 | 25.0 | 78.5 | 6.5 | 4.5 | 11.6 |
| 808-062-089 Matl. No. | 26.0x4.5-15 | | | 1964 190130 | | 4.0 | 26.0 | 81.2 | 6.3 | 4.5 | 10.8 |
| 808-181-089 Matl. No. | 27.0x4.5-15 | | | 1965 197495 | | 4.0 | 27.0 | 84.8 | 7.9 | 4.5 | 13.5 |
| 808-729-089 Matl. No. | 28.0x4.5-15 | | | 1966 189822 | | 4.0 | 28.0 | 89.1 | 7.7 | 5.1 | 12.4 |
| 808-102-089 Matl. No. | 22.0x2.5-17 | | | 1445-9 177193 | | 2.5 | 22.0 | 69.9 | 2.5 | 1.5 | 4.5 |
| 808-130-089 Matl. No. | 22.0x4.0-17 | | | 2404 200268 | | 2.5 | 22.9 | 72.0 | 3.4 | 3.1 | 5.2 |

Eagle Land Speed

| Product Code | Size | Soft To Harder → | | | | Rec. Rim Width* | Overall Diam | Section Width | Tread Width | Weight |
|--------------------------|--------------|------------------|-----------|----------|---------|-----------------|--------------|---------------|-------------|--------|
| | | Hard | Load lbs. | Psi lbs. | Max MPH | | | | | |
| 808-975-090 Matl. No. | 21.0x5.0-15 | 2111 23668 | 1200 | 50 | 300 | 4.5 | 21.3 | 5.4 | 4.1 | 10.0 |
| 808-243-090 Matl. No. | 23.0x5.0-15 | 2283 196199 | 1700 | 70 | 300 | 4.5 | 23.1 | 7.0 | 5.0 | 12.0 |
| 808-028-090 Matl. No. | 25.0x4.5-15 | 2284 196198 | 1700 | 70 | 300 | 4.5 | 24.8 | 6.7 | 4.0 | 12.0 |
| 808-680-089 Matl. No. | 26.0x4.5-15 | 2285 196200 | 1200 | 50 | 300 | 4.5 | 25.4 | 6.5 | 4.5 | 12.0 |
| 808-682-089 Matl. No. | 28.0x4.5-15 | 2286 196215 | 1700 | 70 | 300 | 4.5 | 27.8 | 7.7 | 4.5 | 13.0 |
| 808-329-058 Matl. No. | 8.00/8.20-15 | 2222 194807 | 3000 | 60 | 300 | 9.5 | 28.1 | 13.3 | 9.5 | 21.0 |

Safety Spares

| Product Code | Size | Hard | Application |
|--------------------------|-------|---------------|----------------------------|
| 185-244-515 Matl. No. | PR-16 | 1092 20506 | Tubeless 16" Wide Wheel |

Drag Tire Compound Data

Listed in order from softest to hardest.

*Note that in some cases, a softer compound is not necessarily more tractive due to continual advances in compound technology.

D-2A – For TF/FC and other high horsepower applications.

D-1 – For use on dragsters and other lightweight cars.

D-9 – For use on motorcycles.

D-12 – For use in Stock/SS.

D-4B – For Stock Eliminator. Slightly more tractive than D-4A.

D-4A – Good for hot and/or slick track conditions.

D-4 – Excellent wear/longevity for heavy applications, +3,000 lbs.

D-6 – Works well on dragsters and 1,500 – 2,500 lbs. cars.

D-5 – Works well on 2,000 – 3,200 lbs. cars.

D-7 – Limited application compound. Can help eliminate shake.

D-3 – For heavy cars, +3,000 lbs., both stick and automatic.

| Soft | | Current Compound Selections | | | | | | | | Hard |
|------|-----|-----------------------------|------|------|------|-----|-----|-----|-----|------|
| D-2A | D-1 | D-9 | D-12 | D-4B | D-4A | D-4 | D-6 | D-5 | D-7 | D-3 |

*Acceptable application for rim width is tread plus or minus one inch

- 1 Stiff Sidewall
- 2 High growth construction
- 3 Lightweight construction
- 4 Extended treadlife construction
- 7 Super Stock automatic application
- 8 "Square Corner" tire profile
- 9 Sportsman Front Runner with extended tread life